10-1414 **14" Deluxe Bandsaw**



D/I	\cap	т	\cap	D
IVI	v	и.	v	K

Horsepower	1-3/4 HP TEFC
Amps	14/7
Volts,Hz	115V / 230V, 60Hz

CUTTING CAPACITY

Height	14"	
Width	13-5/8"	

BLADE

Width	3/16" – 3/4"
Length	111"
Speed Range	1,476 / 3,280 ft/min
Supplied on Machine	5/8" x 4 TPI Regular

TABLE

Size	21-1/2" x 15-3/4"
Left Tilt	-7°
Right Tilt	45°
Miter Gauge Slot(s)	(2) 3/4" x 3/8"
Height to Base/Floor	20-7/8" / 40-1/2"
Fence Size	18-3/4" x 1-3/4" x 6"

OVERALL

Height	76"
Width	33-3/4"
Depth	25"
Base Size	24" x 17-5/8"
Dust Port (2)	1 @ 2-1/2" & 1 @ 4"
Net Weight	290 lbs.
Shipping Weight	304 lbs.
Shipping Carton	54-1/2" x 17-7/8" x 23-7/8



14" BANDSAW 10-1414 has many NEW features that woodworkers will enjoy – including NEW SP Coated Table for corrosion protection and reduced friction, NEW Quick Adjust Drift 6" Tall Fence System with Micro-Adustment, NEW enhanced Blade Tension System with quick release blade tension lever, INCREASED 14" Cutting Capacity under the QuickCentric spring-loaded tool-less blade guides, and Two Dust ports. Plus NEW hinged safety Blade Guard with Magnetic Closure and UPDATED Storage Cabinet base. Its dual voltage, 1-3/4 HP motor provides ample power for most everywork encountered. Designed with two NEW speed options – 1,476 / 3,280 ft/min.

STANDARD FEATURES

- NEW 14" Resaw Capacity
- NEW SP Coated Table
- NEW Quick Adjust Drift Fence
- NEW Blade Tension System
- NEW Blade Guard w/Magnetic Door
- NEW 2-1/2" & 4" Dust Ports
- QuickCentric Blade Guides
- UPDATED Storage Cabinet
- FASTER SPEEDS 1,476 / 3,280 ft/min



OUICK-LOCK CAST IRON TRUNNION SYSTEM

- Quick-release blade tension system
- · Large blade tension hand wheel
- · Spring loaded tool-less blade guides
- · Lower wheel dust cleaning brush

ACCESSORIES

MODEL	DESCRIPTION
13-912	Miter Gauge 3/4" x 3/8" T-Slot
13-326	Mobility Kit
C10-391	Table Inserts (Pack 4)
C10-392	Zero Clearance Insert (Pack 4)
C10-395	Aluminum Table Insert
C10-995	Replacement Multi-V Drive Belt
C10-425U	Replacement 14" Urethane Tire
C10-326	Replacement Guide Bearings (Pack of 10)
12-202	LED Gooseneck Work Light with Magnetic Base



BALANCED CAST IRON WHEELS WITH NEW BLADE TENSION DESIGN



SP COATED TABLE FOR **CORROSION PROTECTION** AND REDUCED FRICTION



NEW OUICK ADJUST 6" TALL RIP FENCE SYSTEM WITH MICRO-ADJUSTMENT



To find a dealer or products questions call (877) 884-5167 or visit RIKONTOOLS.COM