RIKON

6" BENCHTOP JOINTER

with Helical - Style Cutterhead

20-600H

Indexible Inserts

12 - 2 sided indexible HSS inserts





Large Fence

Large 19-3/4" x 4-3/8" fence adjusts 90° to 135°

Helical-Style Cutterhead

Has 6 rows with 2 indexible HSS inserts per row

Size.......19-3/4" x4-3/8" Tilt.........90° - 135° Table (*L X W*)........30" x 6-3/16"

Motor

Fence



Cutterhead

Diameter2"	
Speed12,000 RPM	
Number of HSS Inserts (2 sided)12	
HSS Insert Size14.2mm x 14.2mm x 2mm	
Number of Insert Rows6	
Cuts Per Minute36,000 CPM	
Maximum Depth of Cut1/8"	
Maximum Cutting Width6"	
Minimum Length of Stock10"	
Minimum Width of Stock3/4"	
Minimum Thickness of Stock1/2"	
Table Size (2) (L x W)14-3/8" x 6-3/16"	
Dust Port (OD) Diameter2-1/2"	
Dust Collection Minimum CFM100	
Noise Level (No Load) at 3 Feet<100dB	

Switch and Scale

Safety ON/OFF switch with locking key to prevent unauthorized use and an easy to read depth scale

Overall

Height	13"
Width	17-1/2"
Length	30"
Base Size	19" x 9-3/8"
Net Weight	36 lbs.
Shipping Weight	41 lbs.
Shipping Carton31-1/2	
Warranty	



For more information or to find a distributor near you, please visit:

RIKON

AVAILABLE ACCESSORIES 20-600H



12-201

LED Gooseneck Worklight with Magnetic Base and Magnetic Clip



25-593

T25 Mounting Screws for Inserts (10 Pack)



25-410

Optional Planer Stand Plywood/Wood Top Required for Mounting Machine to Stand



25-499

Replacement 2 Sided HSS Inserts (10 Pack)



25-499C

Replacement 2 Sided Carbide Inserts (10 Pack)



For more information or to find a distributor near you, please visit:

www.rikontools.com