20-600HSP 6" Benchtop Jointer with Insert Cutter Head



MOTOR

Amps	10
Volts, Hz	120V, 60Hz
Speed (No Load)	20,000 RPM
CUTTING CAPACITY	
Max. Cutting Width	6″
Max. Depth of Cut	1/8″
Min. Length of Stock	10″
Min. Width of Stock	3/4″
Min. Thickness of Stock	1/2″
Table Size (2)	14-3/8" x 6-1/8"
Overall Table Size	30" x 6-3/16"
Table Height from Base	8-3/8″

CU	TT	ER	H	EA	D	
C						

Speed	12,000 RPM
Number of HSS	12
Inserts (2 sided)	
HSS Insert Size	14.2 mm x 14.2 mm x 2 mn
Number of	б
Cutterhead Rows	
Diameter	2″
Cuts per Minute	72,000
FENCE	
Size	19-3/4" x 4-3/8"
Tilt	90° to 135°
OVERALL	
LxWxH	30 x 17-1/2" x 13"
Base Size (L x W)	19" x 9-3/8"
Dust Port (OD)	1@4"&2-1/2"
Diameter	
Net Weight	39 lbs.
Shipping Weight	42 lbs.
Shipping Carton	31-1/4" x 12-1/2" x 11-1/8"
WARRANTY	5 YEARS

6" BENCHTOP JOINTER 20-600HSP has a 6 row helical-style cutter head with 12 CARBIDE, 2-edge insert cutters for super cutting action, flat surfacing results, and easy knife changes. Features machined aluminum tables with Synthetic Polymer Coating, rigid all-metal construction, a quick depth setting mechanism with scale, adjustable fence that tilts from 90° to 45° quickly and accurately, spring-loaded safety guard, 4" & 2-1/2" dust ports, front safety on/off switch and two push blocks.


FEATURES

• Helical Cutter Head with 12

- Two-sided Carbide Inserts • Large 19 3/4" x 4 3/8" Fence
- Tilts 90° to 135°
- Safety On/Off Switch
- Easy Read Depth ScalePortable at Only 49 lbs.
- Full Table Size 30" x 6-3/16"

ACCESSORIES

MODEL	DESCRIPTION
25-499	HSS 2-Edge Inserts (10 Pack) 14.2 mm x 14.2 mm x 2 mm
25-499C	Carbide 2-Edge Inserts (10 Pack) 14.2 mm x 14.2 mm x 2 mm
25-593	Mounting Screws T25 (10 Pack) for Inserts 25-499, 25-499C
25-410	Steel Stand H. 29-1/4" Top 23" x 14", Base 31" x 22"



HELICAL-STYLE CUTTER HEAD W/ 12 TWO-SIDED CARBIDE INSERTS



ACCESSORY 25-499C CARBIDE 2-EDGE INSERTS (10 PACK)



DEPTH SCALE AND SAFETY ON/OFF SWITCH



LARGE FENCE 19-3/4" x 4-3/8" TILTS 90° TO 135°



*Note: The 20-600HSP Jointer can be mounted on the 25-410 Stand with the addition of a wooden/plywood top (not included).