

10-3062S 10" Deluxe Bandsaw with Stand



MOTOR

Horsepower	1/2 HP
Amps	5.5
Volts, Hz	115V, 60Hz
Speed	1,720 RPM

CUTTING CAPACITY

Height	5"
Width	9-5/8"

BLADE (Includes 5/16" x 6TPI, Regular)

Width	1/8" – 1/2"
Length	70-1/2"
2 Blade Speeds	1,515 / 3,280 ft/min

TABLE

Size	13-3/4" x 12-1/2"
Left Tilt	5°
Right Tilt	45°
Miter Gauge T-Slot	3/4" x 3/8" T-Slot
Height to Floor	39-1/2" (with stand)
Height to Base	14-1/2"
Fence Size	12-1/4" x 2-3/8"

Dust Port	2-1/2" O.D., 2-5/16" I.D.
-----------	---------------------------

OVERALL ON BENCH

H x W x D	34-1/4" x 21" x 13-1/2"
Base Size	15-7/8" x 9-3/8"

OVERALL ON STAND

H x W x D	59-1/4" x 25" x 16-1/2"
Base Size	25" x 18-1/2"

Net Weight	90 lbs.
Shipping Weight	98 lbs.
Shipping Carton	35" x 13" x 17-3/4"

The numerous features of the 10" BANDSAW 10-3062 make it extremely easy to operate and make adjustments to the blade, guides and fence. New SP Coated Table, increased cutting capacity, 2 blade speeds, and increased 1/2 HP motor are quite ample enough for smaller projects, and will be appreciated by woodworkers having limited shop space for a larger size bandsaw. Improved features for easy operation – 2 blade speeds, QuickCentric tool-less blade guides, quick-release blade tension lever, tilting 0-45° cast iron table, adjustable rip fence, larger blade tension knob, dust port for shop vacuum hookup, side windows for viewing blade tracking settings, storage hanger for the fence and tools, and safety paddle on/off switch. Reduced size is ideal for transporting, or storing, when not in use.

NEW REDESIGN FEATURES:

- **NEW SP Coated Table**
- **Easy Fitting Dust Port**
- **Steel Pin Door Hinges**
- **Adjustable Fence Carrier**
- **Easy Sliding Rip Fence System**
- **QuickCentric Blade Guides**
- **Quick-Release Blade Tension Lever**
- **Popular 3/4" x 3/8" Miter Gauge T-Slot**
- **2 Blade Speeds 1,515 or 3,280 ft. / min**
- **Powerful 1/2HP Motor**
- **Cutting Height of 5" and 9-5/8" Cutting Width**

ACCESSORIES

MODEL	DESCRIPTION
13-920	Miter Gauge
C10-393	Replacement Table Inserts (4 Pack)
C10-394	Zero Clearance Inserts (4 Pack)
C10-990	Replacement Multi-V Drive Belt
C10-405U	Replacement 10" Urethane Tire
C10-109	Replacement Guide Bearings (6 Pack)
12-202	LED Gooseneck Work Light with Magnetic Base



STEEL STAND INCLUDED!



TWO BLADE SPEEDS



REDESIGNED ADJUSTABLE FENCE



QUICK-RELEASE BLADE TENSION LEVER

To find a dealer or products questions call (877) 884-5167 or visit RIKONTOOLS.COM